

Emulsion SBR

SBR 1500H

SBR 1500H is a cold emulsion polymerized styrene butadiene copolymer with non-staining stabilizer and especially well-suited for adhesive applications.

It has high internal strength, and excellent shear and peel adhesion. And also it has good processibility, high solubility in solvent and no gel characteristic.

SBR 1500H can be used to conveyor belt and hand-built hose where good building tack and light color are required.

Raw Polymer properties

Polymerization	Cold Emulsion
Volatile matter(%)	0.3
Ash(%)	0.2
Soap(%)	0.1
Organic Acid(%)	6.1
Bound Styrene(%)	23.5
Stabilizer	Non-staining
Mooney Viscosity (ML1+4, 100°C)	52
Color	Light Yellow Bale
Specific Gravity	0.94

Other Features

[Packaging]

Bale weight : 35Kg

Bale wrapping film : LDPE film

[Storage Condition]

SBR 1500H should be stored in a cool and dry place. Exposure to light should be avoided.

* The above data is a typical value, therefore there may be a slight difference between the elements of a supplied product and the data.



- Call center : Tel 82-80-005-4000
- Tech Center : Tel 82-42-860-8351 FAX 82-42-862-1318
- Daesan plant : Tel 82-41-661-2702 FAX 82-41-661-2709
- Seoul H.Q : Tel 82-2-3773-3993 FAX 82-2-3773-3071